

PRO-1515

DLP® Projection System, 12,000 ANSI, Dual Lamp, 5 lens options

Enjoy amazing images from today's sources with Wolf Cinema's latest high performance projection system, the PRO-1515. Boasting 12,000 ANSI of peak white performance and excellent contrast levels, this system can cast razor-sharp images on screens as large as 20' [6.1m] in width. Dual 465W UHP lamps can be run concurrently to achieve maximum peak white output, or can be fired independently and run in "sequential" operating modes, achieving even longer run times between lamp changes. Five primary lenses (three with VariScope™ lens memory system) permit placement in a wide range of custom mounting positions. IR, RS232 and RJ45 capabilities enable system integration capabilities with all major control systems. Choice of black or white case colors.



Specifications:

Imaging Technology	0.95" DarkChip 1080p DLP® Technology by Texas Instruments
Brightness	12,000 ANSI Lumens
Contrast	5,000:1
Lens Shift	+/- 133% Vertical, +/- 50% Horizontal [VariScope™ lenses]
Keystone Correction	±30% Vertical
Lamp Type and Life (hrs)	Dual 465W UHP; Est. lamp life each, 1500 (Normal) / 2000 (Eco)
Noise Level (Eco mode)	Single lamp 37dB; Dual lamp 40dB
Computer Compatibility	WUXGA, 1080p, UXGA, SXGA+, SXGA, XGA, SVGA, VGA; PC and Mac
Video Compatibility	NTSC, PAL, SECAM, 480i, 480p, 576i, 720p, 1080i, 1080p
Video I/O	HDMI v1.4a [2], 3GSDI, DisplayPort, DVI-D, VGA-input, VGA-output, Component video [BNC – RGBHV/Component], S-video, Composite video [RCA]
Control, Other I/O	RS-232C D-sub 9 pin, RJ-45, Ethernet, USB-A [image viewer], USB-B [mini, display over USB]
Dimensions (W x D x H)	20.47" x 23.78" x 7.16" (506 x 604 x 182mm)
Weight	52.5 lbs (23.8kg)
Operating Temperature	40-104°F (5-40°C), 90% max humidity
Voltage	AC Input 100-240V, 50-60Hz, auto-switching
Power Consumption	Dual Lamp Max 1180W (Normal) / 950W (Eco), <0.5W standby mode
Supplied Accessories	AC Power Cord, IR Remote Control, AA Batteries [x 2], Coarse Dust Filters [3 pk], User Manual CD-ROM

Primary Lens Options:

WC-LS-1515-MUZ	Manual Ultra Short Throw Zoom [0.85 – 1.0:1]
WC-LS-1515-MST	Manual Short Throw Zoom [1.0 – 1.35:1]
WC-LS-1515-STV	Short Throw Motorized VariScope™ Zoom [1.20 – 1.50:1]
WC-LS-1515-MTV	Medium Throw Motorized VariScope™ Zoom [1.5 – 2.0:1]
WC-LS-1515-ETV	Extended Throw Motorized VariScope™ Zoom [2.0 – 4.0:1]

Optional Accessories:

WC-PS-03	ProScaler MK III Video Processor with E-VariScope™ Technology
WC-PM-MM	Universal Projector Ceiling Mount Kit, Medium
WC-LPU1515	Replacement 465W UHP Lamp Assembly

Features and specifications subject to change without notice.

DLP is a registered trademark of Texas Instruments. VariScope and E-VariScope are trademarks of Wolf Cinema.