

## PRO-415

### 0.65" DLP®, 1080P, 5000 ANSI, 2D/3D, 5 lens options

Designed for performance and ultra reliability, the Wolf Cinema PRO-415 video projector offers that Wolf Cinema image quality you've come to expect, but at a truly affordable price. Ultra bright 5000 ANSI performance with outstanding black levels delivers a powerful, dynamic image on screens up to 15' [~4.6m] wide. Multiple lens choices facilitate proper projector placement, while ample H/V keystone correction simplifies every installation. IR, RS232 and LAN control, optional 3D glasses and more make this one of the best possible choices for your viewing enjoyment.



#### Specifications:

Imaging Technology	0.65" DarkChip3 1080p DLP® Technology by Texas Instruments
Brightness	5000 ANSI Lumens
Contrast	5,000:1
Lens Options, Lens Shift	5 primary optics choices; maximum shift -20 to +70% V, ±10% H (Manual)
Keystone Correction	± 15° Vertical
Lamp Type and Life [hrs]	370W; est. lamp life 1500 hours (Bright)
Noise Level (Eco mode)	37dB
Audio	3-Watt speaker [1]
Computer Compatibility	HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
Video Compatibility	PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p, 1080p)
Video I/O	HDMI 1.4a with 3D support, DVI-D, DisplayPort, 5BNC, Component Video, VGA - YPbPr/RGB [2], VGA output, S-Video and Composite
Audio I/O Stereo	Stereo L/R RCA audio inputs [2], 3.5mm Mini-RCA audio inputs [2], 3.5mm Mini-RCA audio-output
Control, Other I/O	12V Mini-RCA trigger, RS-232C D-sub 9 pin, RJ-45, USB remote mouse, 3.5mm Mini-RCA wired remote, 3D Sync
Dimensions (W x H x D)	16.9" x 7.1" x 13.4" (430 x 181 x 340mm)
Weight	18.6 lbs (8.44kg)
Voltage	AC Input 100–240V, 50–60Hz, auto-switching
Power Consumption	310W Bright mode / 260W Eco mode (< 0.5W Standby)
Supplied Accessories	AC Power Cord, IR Remote Control, AAA Batteries [x 2], VGA Cable, User manual CD-ROM

#### Primary Lens Options:

WC-LS-415-STF	Fixed Rear/Front [0.77:1]
WC-LS-415-UST	Ultra Short Throw Zoom [1.1 – 1.3:1]
WC-LS-415-ST	Short Throw Zoom [1.54 – 1.93:1]
WC-LS-415-LT	Long Throw Zoom [1.93 – 2.89:1]
WC-LS-415-EL	Extended Throw Zoom [3.0 – 5.0:1]

#### Optional Accessories:

WC-PS-03	ProScaler MK III Video Processor with E-VariScope™ Technology
WC-PM-MS	Universal Projector Ceiling Mount Kit, Small
WC-SD3PK-04	3D starter pack: includes RF emitter and 2 (two) sets of Active 3D Shutter Glasses
WC-SD3DA-04	Active 3D Shutter Glasses, RF
WC-LPU370	Replacement 370W UHP Lamp Assembly

*Features and specifications subject to change without notice.  
DLP is a registered trademark of Texas Instruments. VariScope and E-VariScope are trademarks of Wolf Cinema.*